Bona Hard Wax Oil

Technical data sheet

Natural oil, modified for superior protection of wooden floors. Produces the warm look of an oiled floor while establishing a hardwearing and stain resistant surface that is spot-repairable and easy to maintain. Unique composition formulated without controversial substances such as cobalt and ketoximes. Very low in odour and easy to handle, being applicable with roller, brush and trowel. Leaves an open, breathing surface that reduces the risk of side-bonding. Highly suitable for floors with underfloor heating.

Should you wish to transform your floor with a new colour then simply prepare the surface with Bona Craft Oil and/or the Bona Rich Tone before sealing with 1 -2 layers of Bona Hard Wax Oil.

- Extreme water resistance
- Rapid drying, fast working process
- Inhibits risk of side-bonding
- High coverage rate
- Safe for application on children's toys and countertops, EN 71-3 compliant

Technical data

Product base: Modified vegetable oils and waxes

Solids content: approx. 48%

Sheen (at 60°): Silkmatt: ≈20, Matt: ≈10, XM: ≈3

Dilution: Do not dilute

Drying time: - Before sanding/recoating: 6-8 hours*

- Light use: min 16 hours*

*under normal indoor conditions, 20 ℃/60% R.H. Ensure proper

ventilation.

Application tool: Short-haired mohair roller or good quality brush with tightly

packed fine bristles.

Application rate: 20-24 m² per litre and layer.

Clean tools with white spirit. Dried material can be removed with

acetone.

Safety: Classified, see safety data sheet for more information.

Fire risk: Non-flammable. Risk of self-ignition, see safety data sheet for

more information.

Shelf life: 3 years, from date of production, in unopened original container. Storage: Store between +5°C and +25°C in a cool, well-ventilated area

away from incompatible materials and ignition sources.

Disposal: Wastes and emptied containers should be handled in

accordance with local regulations.

Pack size: 6 x1 litre

2 x 2,5 litres 1 x 10 litres





