

BONA
DECKING OIL



Create **your** own wood **story**

BONA OIL SYSTEM – UNIQUE CHARACTERS ON WOODEN FLOORS



Natural solutions for healthy floors

Bona's complete range of oils are renewable, made using raw vegetable materials and contain exceptionally low levels of VOC and contains no hazardous agents such as cobalt and ketoximes. Their high oil content ensures a high degree of saturation with fewer applications for healthy floors and long-lasting protection.

- ✓ Natural solutions
- ✓ Child safe
- ✓ Cobalt free

Bona Decking Oil

Long-lasting protection for outdoor decks

Bona Decking Oil provides outdoor decking with long-lasting protection against the challenges of rain, freezing snow and scorching sun. Its unique formula enhances the natural wood grain, while reducing the potential of wood cracking, warping and protecting against moisture ingress. Bona Decking Oil also contains UV protection against bleaching. With easy application and a fast drying time, it is your perfect partner for outdoor decking protection.

COLOUR VERSIONS



Neutral



Mahogany



Teak



Grey



White

APPLICATION

Bona Decking Oil is suitable for decking and other exterior wood surfaces.

KEY BENEFITS

- Long-lasting all weather protection
- UV protection
- Reduces wood cracking and warping
- Easy application and fast drying
- Low VOC content and low odour

TECHNICAL DATA

Product base: Modified vegetable oil
VOC: ~ 6%
Dilution: Do not dilute

TECHNICAL DATA (CONTINUED)

Drying time: Between applications: 30-60 minutes*
 Light use: 24 hours*
*under normal indoor conditions, 20°C/60% R.H. ensure proper ventilation.

Application tools: Brush, roller or other suitable applicator

Total consumption: Approx. 20 m²/litre depending on wood type and application

Fire risk: Non-flammable. Risk of self-ignition, see safety data sheet for more information

Cleaning: Use clean tools with white spirit and dried material can be removed with white spirit

Shelf life: 2 years, from the date of production, in unopened original container

Storage/transport: The temperature must not fall below +5°C or exceed +25°C during storage and transport

Disposal: Waste and emptied containers should be handled in accordance with local regulations

Sizes: 2 x 2.5 litres
 1 x 10 litres (only Neutral)