



Bona R850T



Bona R850T

Bona R850T is an elastic 1-component Silane based adhesive for parquet floors according to EN 14293 (soft). The hardened adhesive is - similar to conventional adhesives - able to withhold thrust during expansion, while the resistance against shrinkage is very low. Tensions to the sub floor are therefore reduced. The use of a primer is in general not necessary. The adhesive hardens by a chemical reaction with moisture.



Key Benefits

- 1-component, easy to handle
- soft elastic
- Water and solvent free, nearly no swelling of the wood
- Good adhesion to almost all substrates and timber materials, splashed material can be easily removed
- Firm texture – retains trowel pattern

Technical Data

| | |
|----------------------|---|
| Base: | Silane modified-Prepolymere |
| Colour: | Cream |
| Viscosity: | Easy to apply - stable |
| Density: | 1.51 g/cm ³ |
| GISCODE: | RS 10 |
| Ecode: | EC1R |
| Cleaning agents: | S100, acetone and ethanol. Hardened adhesive can only be removed mechanically. |
| Application of load: | 24 to 48 h |
| Surface treatment: | Depending on air humidity and the moisture content of the materials between 2 and 4 days. |
| Storage / transport: | The temperature must not fall below +5°C or exceed +25°C during storage and transport. Store in a cool, dry, well ventilated place. |
| Shelf life: | 6 months. |
| Pack size: | 600 ml / 0.96 kg per tube, 20 tubes per carton |

Additional detailed information is noted in the appropriate Safety Data Sheet.