



Beating Time

Bona Traffic HD – Powerful performance at top speed



Beating Time

Bona Traffic HD – Powerful performance at top speed

Bona Traffic HD, the high-performance finish for high-traffic areas, now delivers superior protection in less time than ever before, outperforming any other finish in terms of speed and durability.

Experience unparalleled wear resistance and minimized downtime. Floor owners are now able to get back on the floor already 12 hours after application.

Bona Traffic HD is a powerful solution for areas such as lobbies, airports, exhibition halls and train stations, giving your floors long-lasting protection and preserving its beauty for its entire lifetime.



Application

Designed to last, Bona Traffic HD ensures ultimate durability for extremely high-traffic areas.

- Heavy-traffic floors: airports, hotels, shopping malls etc.

Key Benefits

- Ultimate durability
- Minimises downtime – back on the floor in 12 hours
- Low VOC < 5%
- Extremely low odour
- Non-yellowing surface
- DIBt approved
- Excellent absorption of floor unevenness
- Improves adhesion of over lacquer

Gain for the contractor

- Faster curing saves valuable time for both contractors and floor owners
- Improved working conditions

Technical Data

Type of varnish:	2-component waterborne polyurethane topcoat
Solids content:	~32%
VOC:	max 52g/litre (incl. hardener)
Resistance to wear:	1-2 mg/100 revolutions (SIS 923509)
Sheen (at 60°):	Silkmatt 40-45%, Matt 20-25%, Extra Matt ~10%
Mixing ratio:	1 part Bona Traffic HD Hardener to 10 parts Bona Traffic HD
Pot life:	4 hours at 20°C (shorter if warmer)
Dilution:	If required, dilute with 4% Bona Retarder for a longer open time
Drying time, until sanding/recoating:	- Ready in 2-3 hours* - Full use: 24 hours* - Full hardness: 5 days* *under normal climate conditions, 20°C/60% R.H.
Application rate:	8-10 m ² /litre (120-100g/m ²) per coat
Safety:	Varnish: Unclassified Hardener: Classified (see Safety Data Sheet)
Cleaning:	Clean with water. Dried material can be removed with acetone.
Shelf life:	1 year from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Pack size:	3 x 4.95 litres incl. hardener