

Technical Data Sheet

Bona D700

D3 White Glue

Bona D700 is solvent-free white glue which meets the requirements of class D3 according to EN 204 and is suitable for gluing various timber materials, especially tongue and groove pre-finished parquet, laminate floor coverings or similar materials. It sets quickly and has a good resistance to water.

- Good resistance to water
- Rapid setting
- Good open time
- Universal applicability

Technical Data

Product type: Dispersion of polyvinyl acetate

Colour: White

Viscosity: Viscous

Density: 1.09 g/cm³

Cleaning agent: Water

Storage / transport: The temperature must not fall below +5°C or exceed +25°C during storage and transport. Protect from frost

Store in a dry, well ventilated place.

Shelf life: 12 months from date of manufacture in an unopened bottle

Pack size: 0.75 KG bottle

Additional detailed information is noted in the appropriate Safety Data Sheet.

Subfloor Preparation

Not applicable

Suitable Subfloors

Not applicable

Processing

Before using the glue the following climatic conditions must be met (values for Central Europe):

- Air temperature: min. 15°C
- Material temperature: min. 15°C

Apply the glue to the upper surface of the tongue. Then join the boards together and, if necessary, knock together with a hammer. The correct amount of glue has been used if a small amount penetrates the joint between the boards. From ready-to-lay parquet and laminate floor coverings, excess glue must be removed immediately with a moist cloth.

Consumption

Approx. 5-30 g/running meter according to the size of joints

Drying time

approx. 24 hours, depending on the type of parquet, absorbency of the substrate and room climate, it is possible to sand the floor, apply a surface coating, etc

Bona takes only responsibility for the delivered product, no responsibility can be taken for the total installed product. If in doubt, conduct a test or a trial. Observe also other Bona product datasheets.

04.09.2018

With the publication of this data sheet all previous product information on this product lose their validity

Fastening

