

Bona Quick

Technical data sheet

A high viscous primer with a gel-like consistency. Use as first layer on untreated wood, without following abrasion. Use between coats of finish, to reduce abrasion scratches and fill small irregularities for a flawless end-finish. Bona Quick typically produces a light wood colouration but the final colour depends on the choice of topcoat.

- Quick drying gel
- Reduces scratches
- First layer and/or in-between coats
- Easy trowel application
- GreenGuard approved for low indoor emissions

Technical data

Type of lacquer:	Waterborne 1-component trowel primer
Solids content:	Approx. 40%
Dilution:	Do not dilute
Drying time:	1-2 hours at 20°C/60% R.H.
Application tools:	Stainless steel trowel
<u>Application rate:</u>	
- Untreated wood	25-35 m ² /lit (40-30g/ m ²) per coat
- Between coats	approx. 50 m ² /lit (20g/ m ²)
Safety:	Unclassified
Cleaning:	Wipe tools free from residual material before cleaning with a minimum of water. Dried material can be removed with acetone.
Shelf life:	1 year from date of production in unopened original container
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport
Pack size:	5 litres
Certifications:	GreenGuard DIBt; safe building product

Preparations

Ensure floor is acclimatized to its end-use environment. The surface which is to be treated must be sanded back to bare wood, dry and free from sanding dust, oil, wax and other contamination. It is recommended to finalize the sanding with a Bona Quattro or Multi Disc.

Allow product to reach room temperature. Optimal application conditions are between 18-25 C and 30-60% relative air humidity. High temperatures and low humidity shorten, low temperatures and high humidity lengthen drying time. **Minimum temperature for use is 13°C.**

Treatment schedule

Untreated wood: 3x Bona Gel 2-3x Bona Lacquer	Between coats: 1-2x Bona Gel
--	--

Finishing



Bona[®]

Bona Quick

Technical data sheet

Finishing



Application

1. Apply the primer using a stainless steel trowel. Ensure that no strings of primer are left behind.
2. Allow to dry and then apply a second layer in the opposite direction of the first layer.
3. Let dry and apply a third and final layer.

Normally no grain raising occurs and abrading is therefore unnecessary. If a mid-abrasion is required then this should be done on the first top coat and not directly on Bona Gel.

Maintenance

Bona Gel should never be used as the final treatment for timber floors

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a preliminary test. User is required to read and understand all information contained on package labels and safety data sheets before using this product.