

Bona Shield W

Technical data sheet

Maintenance coating based on Bona Lacquer technology, specifically developed for wooden floors. Easy to apply without requiring any buffing. Repeated use actively extends the durability of the surface and prevents premature wear-through.

- High durability
- Quick drying
- Comfortable friction

Technical data

Type of coating:	Matt = Acrylate/Polyurethane, Gloss = Polyurethane
Sheens:	Matt & Gloss
Dilution:	Do not dilute
Drying time:	1-2 hours at 20°C/60% R.H.
Application tools:	Bona Applicator Pad
Application rate:	30-50 m ² /litre
Safety	Unclassified
Cleaning:	Clean tools in soap and water. Dried stains can be removed with Bona Remove W.
Shelf life:	2 years from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size	6x1 litre, 3x5 litres

Preparations

Preparation: Clean surface according to the degree of soiling using Bona Clean W10. If a more aggressive cleaner is needed, use Bona DeepClean W. Note that any residual dirt will remain trapped in the coating. It is recommended to test adhesion prior to use, especially if the history of the floor is unknown. Wax and certain types of polishes may conflict adhesion. Full stripping of the old maintenance coating is in such case necessary. See Bona Remove W for instructions.

Application

1. Shake container thoroughly before use.
2. Pour product onto floor and distribute, in a systematic manner, a thin, even coat across the entire surface.
3. If required, it is possible to apply a second layer of polish after 1-2 hours. Careful foot traffic is also possible after this time.

Maintenance

Clean floor on a regular basis using Bona Clean W10. Observe respective technical data sheets and the separate instructions for care and cleaning.

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a preliminary test. User is required to read and understand all information contained on package labels and safety data sheets before using this product.

