

Bona Wax Oil W

Technical data sheet

Durable wax oil for periodic maintenance of oiled and hardwax oiled surfaces. Restores dry oiled floors and adds a protective layer of wax for increased resistance to water and spills. Consists of a concentrate of natural oils and waxes, containing less than 2% solvents.

- Restores and protects
- Low solvent content and low odour
- Safe for application on children's toys and countertops, EN 71-3 compliant

Technical data

Type of oil:	Emulsified vegetable oils and waxes
Solids content:	Approx. 70%
VOC:	<2%
Dilution:	Do not dilute
Drying time:	- Light use: 12 hours* <i>*under normal indoor conditions, 20 °C/60% R.H. Ensure proper ventilation.</i>
Application tools:	Bona WoolPad or stainless steel trowel
Total consumption:	Approx. 50-80 m ² /litre depending on wood type
Safety:	Unclassified
Fire risk:	Non flammable. Risk of self ignition, see safety data sheet for more information.
Cleaning:	Clean tools with white spirit. Dried material can be removed with white spirit.
Shelf life:	3 years, from the date of production, in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Sizes:	6 x 1 litre

Preparations

If necessary, the previously oiled/hard wax oiled surface must be thoroughly cleaned using Bona Oil Soap or the Bona DeepClean W and allowed to dry before applying Bona Wax Oil W. Allow product to reach room temperature and shake the container thoroughly before use. **Minimum temperature for use is 16°C.**

Application

1. Apply the Wax Oil W thinly using a Bona WoolPad or a stainless steel trowel.
2. Remove surplus Wax Oil Refresher with cotton cloths straightaway and let dry min 12 h, expect longer drying time on exotic wood and at low temperatures.

WARNING: BONA WAX OIL REFRESHER CONTAINS DRYING OILS. RISK OF SELF-IGNITION. USED CLOTHS, RAGS AND SIMILAR SHOULD BE PLACED IN WATER OR SEALED METAL CONTAINERS.

Note: The oil may contain particles of wax. This is normal. The wax is softened and smeared out during the buffing process.

Bona
Care



Bona[®]

Bona Wax Oil W

Technical data sheet

Bona
Care



Maintenance

Clean the floor regularly using a dry mop and/or a vacuum cleaner. When needed, wipe off with a damp mop with Bona Oil Soap added to the cleaning water. Always clean using as dry a method as possible. Apply Bona Wax Oil W frequently to ensure that the pores of the surface remain saturated and unable to pick up dirt and moisture. The frequency of this operation is determined by the level of wear and may range from every 3rd year in a domestic environment to a few times a year in a commercial setting.

Detailed maintenance instructions are available at www.bona.com

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a

Bona Wax Oil W

Technical data sheet

preliminary test. User is required to read and understand all information contained on package labels and safety data sheets before using this product.

Bona
Care

