

# DriFast® Stain

## Technical data sheet

A premium quality quick-drying stain for interior hardwood floors, DriFast Stain's advanced technology formula provides speed and high performance for hardwood floor finishing professionals. Compatible with all Bona® waterborne systems and all other Bona® finish systems.

- 2 hour dry time\*
  - No bleed back
  - Penetrates, stains, and seals bare wood
  - 800-1,000 sq ft/gal coverage rate
  - Available in 25 wood tones and white
  - All stain colors can be blended, offering an endless color palette
  - Clean up with mineral spirits
  - Easy touch-ups (mineral spirits for thinning dark or heavy spots)
- \*6 hours minimum for white and 12-18 hours for Ebony, Spice Brown, Bark and Cocoa under ideal conditions of 60°-80° F(16°-27°C) with 35-75% relative humidity.

### Technical data

#### Physical Characteristics:

**Ingredients** – Wood tones: Oil-modified resins, mineral spirits (solvent), pigments, driers

**White:** Oil-modified resins, mineral spirits (solvent), titanium dioxide, fillers

**Colors** – Wood tones: Natural, Golden Oak, Nutmeg, Early American, Provincial, Special Walnut, Rosewood, Red Mahogany, Jacobean, Graphite, Medium Brown, Antique Brown, Puritan Pine, Cherry, Sedona Red, Spice Brown, Grey, Ebony, Bark, Cocoa, Driftwood, Birch, Aged Pewter, Twig and Sand Dune.

**Solids** – 35-47%

**Density** – Wood tones: 7.2-7.5 lbs/gallon (0.86-0.90 s.g.), White: 8.7-9.0 lbs/gallon (1.04-1.8 s.g.)

**US Regulatory VOC** – 550 g/L

**Odor** – Mild solvent odor

**Stability** – Two-year shelf life in unopened container

**Flashpoint** – 116.6°F (47°C)

**Packaging** – 1-quart cans, 1-gallon cans

#### Application Characteristics:

**Clarity** – Semi-transparent (dry)

**Drying Time** – 2 hours for wood tones, 6 hours minimum for white and 12-18 hours for Ebony, Spice Brown, Bark and Cocoa under ideal conditions of 60°-80° F(16°-27°C) with 35-75% relative humidity.

**Coverage** – 800-1,000 square feet per gallon

**Application Tools** – Clean cloths, brush, cut-in pad

### Recommended Use

- Apply only over bare wood
- Prepares the surface for a topcoat of Bona® waterborne or any other Bona® finish

### Directions

#### BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS.

**FOR TECHNICAL ADVICE:** Call Bona US at 800-872-5515

**COMPATIBILITY:** Stain, sealer and finish results may vary widely depending on the wood species, especially on oily and resinous Exotics. ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.

**SANDING AND PREPARATION OF NEW FLOORS:** 1. Sand and prepare floor using accepted industry association methods. 2. Make your final cut with 80-100 grit paper and MultiDisc with 80-120 grit. 3. Use a Tampico Brush on a buffer and vacuum thoroughly. 4. Tack with a dry Bona® Microfiber Mop or cloth to remove dust. 5. Apply stain system.

**THE BONA® DRIFAST® STAIN SYSTEM:** Bona DriFast Stain is a redissolving stain designed to penetrate, stain and seal bare wood. Bona DriFast Stain is designed to work with all Bona finishes. Colors may be blended with all other Bona DriFast Stains. Visit [www.bona.com](http://www.bona.com) for additional product information.

**RECOMMENDED APPLICATORS & TOOLS:** Brush, cut-in pad, cloth, carpet disc

**MIXING INSTRUCTIONS:** Shake and stir well before using. Do not thin.

## Finishing



# Bona®

# DriFast® Stain

## Technical data sheet

**STAINING:** 1. After preparing surface, apply Bona DriFast Stain with brush, cut-in pad, cloth or carpet disc driven by a buffer in the direction of the grain at the coverage rate of 800 – 1000 square feet per gallon. 2. Allow 1-3 minutes for penetration. Remove excess by hand wiping or buffing with an absorbent, non-abrasive material. 3. Allow stain to dry thoroughly (minimum 2 hours for wood tones, 6 hours minimum for white and 12-18 hours for Ebony, Spice Brown, Bark and Cocoa under ideal conditions of 60°-80° F(16°-27°C) with 35-75% relative humidity. High humidity and/or low temperature conditions will extend dry time, while increased ventilation and airflow will reduce dry time. Apply sealer or finish after the recommended dry time, but within 48 hours after application. 4. Apply any Bona finish system over thoroughly dried stain.

**DANGER:** RAGS, STEEL WOOL OR WASTE SOAKED WITH BONA DRIFAST STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED, METAL CONTAINER.

### Maintenance

**CLEAN-UP:** Clean application tools and equipment with mineral spirits.

**STORAGE AND DISPOSAL:** Store at room temperature. Keep container closed when not in use. Do not store above 100°F (38°C). Do not transfer contents to other containers for storage and disposal. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

### Order Information

Item #	Size / Color	#/Case
SS750051100	Quart – Natural	6
SS750051101	Quart – Nutmeg	6
SS750051102	Quart – Golden Oak	6
SS750051103	Quart – Early American	6
SS750051104	Quart – Provincial	6
SS750051105	Quart – Special Walnut	6
SS750051106	Quart – Rosewood	6
SS750051107	Quart – Red Mahogany	6
SS750051108	Quart – Jacobean	6
SS750051109	Quart – Graphite (formerly Ebony)	6
SS750051110	Quart – White	6
SS750051111	Quart – Medium Brown	6
SS750051112	Quart – Antique Brown	6
SS750051113	Quart – Puritan Pine	6
SS750051114	Quart – Cherry	6
SS750051174	Quart – Spice Brown	6
SS750051175	Quart – Sedona Red	6
SS750051176	Quart – Grey	6
SS750051177	Quart – Ebony	6
SS750051178	Quart – Bark	6
SS750051179	Quart – Cocoa	6
SS750051180	Quart – Driftwood	6
SS750051181	Quart – Birch	6
SS750051182	Quart – Aged Pewter	6
SS750051183	Quart – Twig	6
SS750051184	Quart – Sand Dune	6
SS750018100	Gallon – Natural	4
SS750018101	Gallon – Nutmeg	4
SS750018102	Gallon – Golden Oak	4
SS750018103	Gallon – Early American	4
SS750018104	Gallon – Provincial	4
SS750018105	Gallon – Special Walnut	4
SS750018106	Gallon – Rosewood	4
SS750018107	Gallon – Red Mahogany	4
SS750018108	Gallon – Jacobean	4
SS750018109	Gallon – Graphite (formerly Ebony)	4
SS750018110	Gallon – White	4
SS750018111	Gallon – Medium Brown	4
SS750018112	Gallon – Antique Brown	4
SS750018113	Gallon – Puritan Pine	4
SS750018114	Gallon – Cherry	4
SS750018160	Gallon – Ebony	4
SS750018161	Gallon – Grey	4
SS750018166	Gallon – Spice Brown	4

## Finishing



**Bona®**

# DriFast® Stain

## Technical data sheet

SS750018165	Gallon – Sedona Red	4
SS750018167	Gallon – Bark	4
SS750018168	Gallon – Cocoa	4
SS750018169	Gallon – Driftwood	4
SS750018170	Gallon – Birch	4
SS750018171	Gallon – Aged Pewter	4
SS750018172	Gallon – Twig	4
SS750018173	Gallon – Sand Dune	4



## Finishing

