

Maintenance Instructions

Below is a complete list of available maintenance instructions, along with abbreviations to help you identify and select the right treatment.


WH-C	Wood Hard Wax Oil Cleaning
WH-DC	Wood Hard Wax Oil Deep Cleaning
WH-P	Wood Hard Wax Oil Protecting
WH-RC	Wood Hard Wax Oil Recoating
WL-C	Wood Lacquered Cleaning
WL-DC	Wood Lacquered Deep Cleaning
WL-P	Wood Lacquered Protecting
WL-RC	Wood Lacquered Recoating
WO-C	Wood Oiled Cleaning
WO-DC	Wood Oiled Deep Cleaning
WO-P	Wood Oiled Protecting
WO-RC	Wood Oiled Recoating
WS-C	Wood Sport Cleaning
WS-DC	Wood Sport Deep Cleaning
WS-P	Wood Sport Protecting
WS-RC	Wood Sport Recoating
WD-DC	Wood Decking Deep Cleaning
WD-P	Wood Decking Protecting
WD-RC	Wood Decking Recoating

Cleaning Instructions

Oiled Wood Flooring

Part of the Bona Care Program

WO-C



© A.I.S.E

Dry cleaning - loose dirt

- Vacuum or sweep using a Bona Dusting Pad.
- Remove spills and stains with Bona Spray Mop.



Moist cleaning - Stubborn dirt

- Dampen a Bona Cleaning Pad with a solution of Bona Oil Soap and water (2 dl to 10 litres).
- Wipe and work in the direction of the wood.




Deep Clean Instructions

Oiled Wood Flooring

Part of the Bona Care Program

WO-DC



Bona PowerScrubber combined with Bona DeepClean W cleans oiled wood floors quickly and effectively. Deep cleaning is not a standalone procedure, as some of the surface protection is removed in the process, therefore new oil should be applied after deep cleaning, as described in process WO-P.

- Attach red brushes to the Bona PowerScrubber.
- Fill the tank with 0.5 litres of Bona DeepClean W and 9.5 litres of water.
- Set the contact pressure to medium.
- Run the machine, cleaning in a systematic way. Wipe away residual solution immediately using a mop. After cleaning, place the machine on a water-resistant surface.
- Allow the surface to dry and follow with an application of Bona Oil Care (as described in process WO-P).




Protecting Instructions

Oiled Wood Flooring

Part of the Bona Care Program

WO-P



© A.I.S.E

Periodic re-oiling prevents the wood pores from absorbing water and dirt for easier cleaning maintenance. This can be done in 2 ways, depending on the level of soiling.

Lightly soiled

- Clean the floor manually or with a machine using a solution of Bona Oil Soap and water (2 dl to 10 litres of water).
- Allow the surface to dry.
- Apply a thin coat of Bona Oil Care (30-50m²/lit) to a section of the floor (10-20m²), using a Bona Oil Squeegee.
- Fit a green pad to the buffing machine (150 rpm) and run it over the wet oil.



1:50



© A.I.S.E



© A.I.S.E

- Remove surplus oil with cotton cloths, either manually or by wrapping the cloth around a pad on the buffing machine.
- Allow to dry for approx. 12 hours prior to use.

Heavily soiled

- Attach red brushes to the Bona PowerScrubber.
- Fill the tank with 0.5 litres of Bona DeepClean W and 9.5 litres of water.
- Set the brush contact pressure to medium.
- Run the machine and clean in a systematic way. Wipe away residual solution immediately using a mop. After cleaning, place the machine on a water-resistant surface.
- Allow the surface to dry.
- Pour approx. 1 dl of Bona Care Oil (40-60 m²/lit) on the floor and distribute using a Bona Wool Pad fitted to the buffing machine. Add more oil as required.



1:20



© A.I.S.E

- For best results, buff the floor a final time using a dry Bona Wool Pad.
- Allow to dry for approximately 12 hours prior to use.

For more information visit bona.com

Bona®