



Bona Home **Construction Adhesive**

Part of the **Bona Home** wood floor renovation system

Bona[®]



Bona Home Construction Adhesive

- Quick bonding and curing
- High strength
- Outstanding adhesion

Hard-elastic construction adhesive based on silane. Will not run or contract. Bonds and sets quickly. Remains flexible. Contains no plasticizers, isocyanates, water or solvents. For indoor use.

Compatible materials:

- Wood and wood-based materials
- Mineral materials such as stone
- Ceramics
- Materials containing cement
- Gypsum-based materials



TECHNICAL DATA

Basis:	Elastic, 1-component, silane-modified construction adhesive	Drying time:	4-8 hours
Delivery form:	310ml	Storage:	Frost-free
		Shelf life:	2 years

PREPARATION:

The surfaces to be bonded must be clean, free of grease, dry and firm. If unsure, please test adhesion prior to use. Ensure that the

adhesive and all materials to be bonded are at a temperature of at least 5 °C.

APPLICATION:

Open the cartridge and attach the nozzle. Cut the nozzle to the preferred size. Apply the adhesive to one of the materials to be bonded, then join the components together within 10 minutes.

Strong adhesion is usually achieved after 1 hour. Full adhesion is achieved after 4-8 hours depending on the temperature and the moisture content of the materials.

THE BONA HOME WOOD FLOOR RENOVATION SYSTEM

Just like any other renovation project, renovating wood flooring can be a challenge. Knowing exactly what has to be done is the key to superb results. This is why we have devised a step-by-step system comprising products and instructions to guide you through

the entire renovation process. Step by step for wood flooring that looks just like new. Find out more at bona.com or at your local hardware shop. Bona Home – your wood floor renovation system