



BONA PRIME TROWEL

Product Description

Features

Bona Prime Trowel is a one-component waterborne base coat designed for application with trowel. It is intended to be used on hardwood and other wooden floors prior to overcoating with Bona waterborne finishes. Bona Prime Trowel forms a thick, dense film that the top coat will not penetrate. Normally no grainraising occurs and abrading is therefore unnecessary.

- Fast system
- High build
- Leaves a clean, smooth surface

Technical Data

| | |
|--------------------------|---|
| Type of finish: | Waterborne trowel primer |
| Solids content: | Approx. 40% |
| Mixing ratio: | The primer is 1-component and ready-to-use |
| Drying time: | 10-15 minutes at 20°C / 60% R.H. |
| Application tools: | Stainless steel trowel |
| <u>Application rate:</u> | |
| - On bare wood | 25-35 m ² /litre (40-30g/m ²) per coat |
| - Between coats | approx. 50 m ² /litre (20g/m ²) |
| Safety: | Unclassified |
| Flash point: | Non-flammable |
| Shelf life: | 1 year from date of production in unopened original container |
| Storage/transport: | The temperature must not fall below +5°C or exceed +25°C during storage and transport |
| Disposal: | Wastes and emptied containers should be handled in accordance with local regulations. |
| Pack size: | 3 x 5 litres (44 boxes per pallet) |