



Bona Anti-Slip Additive

Provides improved slip resistance on wet or dry surfaces



Achieve additional slip protection when added to Bona Pure HD without additional time during the coating process. One bag (5.3 oz.) treats one gallon of topcoat.

- Easy to apply
- One or two coat application for additional slip resistance



Bona Anti-Slip Additive

Provides improved slip resistance on wet or dry surfaces

PHYSICAL CHARACTERISTICS

Ingredients – Polypropylene granules
Color – White in packaging, clear when added to the finish.
Solids – 100%
Shape – random
Size – 50 mesh
Materialism - Nonmetameric
Packaging – 1-pound in (3) 5.3-ounce bags

APPLICATION CHARACTERISTICS

Application Tools – Stir stick or paddle mixer
Coverage – Each 5.3 OZ. package treats one gallon of Resilient Floor Finish.

RECOMMENDED USE

Use together with Bona Pure HD on VCT, linoleum, PVC, LVT and rubber floors.

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS.

FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

APPLICATION

Mix one package of Bona® AntiSlip Additive to one-gallon bucket of Bona Pure HD. Stir well. Periodically stir material to keep additive in suspension. For best results, always topcoat with Pure HD. **NOTE:** if additional slip protection is needed, a second coat of Bona AntiSlip Additive in Pure HD.

STORAGE

Nonflammable — Bona Commercial System Resilient Floor AntiSlip Additive should be stored in a climate-controlled environment.

ORDERING INFORMATION

Item #	Description	Size	No/Case	Weight/Lbs.
AX0003605	Bona AntiSlip Additive	5.3 oz.	3	1.1