



Bona Deep Clean Polish Remover

Removes acrylic based polishes that have been applied onto polyurethane finished wood floors



Bona Deep Clean Polish Remover™ is design for the removal of acrylic based polishes that have been applied onto polyurethane finished wood floors. After application the treated floor can be laeft as is or re-coated with another acrylic based polish.

- Perfect way to remove years of polish build-up
- Won't damage the original finish of the hardwood floor
- Works great with the Bona PowerScrubber®



Bona Deep Clean Polish Remover

Removes acrylic based polishes that have been applied onto polyurethane finished wood floors

PHYSICAL CHARACTERISTICS

Ingredients – Water, diethylene glycol monobutyl ether, phenoxyethanol, dipropylene glycol n-butyl ether, and nonionic surfactant.

Color – Tan (wet)

pH – 10-11

Solids – 2.0-3.0

Density – 8.4 lbs./gallon (1.01 kg/L)

US Regulatory VOC - <3%

Odor – Non-Offending - slight solvent odor

Stability – 1 year shelf life in unopened container

Packaging – 1-gallon plastic bottle

APPLICATION CHARACTERISTICS

Drying Time – 15-20 minutes

Application Tools – Bona® PowerScrubber™, Auto scrubbers

RECOMMENDED USE

For removal of acrylic based polishes from polyurethane finished wood floors. Once polish is removed floor may be coated with polish. Once polish is removed floor may not be coated with a urethane finish due to adhesion failure.

DIRECTIONS

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEET.

MIXING INSTRUCTIONS: Gently rock bottle back and forth for 30 seconds

APPLICATION DIRECTIONS:

Using the Bona PowerScrubber®

1. Apply Bona DC Polish Remover™ evenly over a small section of floor (40-60 square feet) 2. Apply at a rate of 700 – 800 square feet per gallon 3. Allow Bona DC Polish Remover™ to dwell on the floor for 5-7 minutes 4. Do not allow Bona DC Polish Remover™ to dry on the floor, apply more to areas that are drying

prior to the 5-7-minute dwell time 5. Using the Bona PowerScrubber® fitted with the standard soft white cleaning brushes and filled with Bona Deep Clean Solution® (mixed per bottle instructions) thoroughly clean the area Bona DC Polish Remover™ was applied to 6. Depending on the amount of polish to be removed, it may be necessary to repeat steps 1-5 7. Repeat steps 1-5 on the remainder of the floor, working in small sections until all polish has been removed

Without the use of the Bona PowerScrubber®

1. Apply Bona DC Polish Remover™ evenly over a small section of floor (40-60 square feet) 2. Apply at a rate of 700 – 800 square feet per gallon 3. Allow Bona DC Polish Remover™ to dwell on the floor for 5-7 minutes 4. Do not allow Bona DC Polish Remover™ to dry on the floor, apply more to areas that are drying prior to the 5-7-minute dwell time 5. Using a brown scrubbing pad, driven with a 175-rpm buffer, agitate the area treated with Bona DC Polish Remover™ 6. Clean/mop the treated area using a microfiber cleaning pad, to remove polish residue from the floor 7. Depending on the amount of polish to be removed, it may be necessary to repeat steps 1-6 8. Repeat steps 1-6 on the remainder of the floor, working in small sections until all polish has been removed Wet tack entire floor to remove any drips or wet spots auto scrubber may have missed.

CLEAN-UP

Clean all tools and equipment with warm water.

ORDERING INFORMATION

Item #	Description	Size	No. Case	Weight/ Lbs.
WM772018001	Bona Deep Clean Polish Remover	Gallon	2	18.45