Technical Data Sheet



Bona[®] Professional Series Stone, Tile & Laminate Floor Refresher

Professional-level, acrylic coating formulated to keep, sealed hard-surface floors looking new



Bona[®] Professional Series Stone, Tile & Laminate Floor Refresher provides a clear, highly durable gloss to all sealed hard surface flooring including laminate flooring, vinyl, no-wax linoleum, terrazzo, unglazed tile (ceramic, Mexican Saltillo, quarry), stone, and sealed porous marble. Waterborne acrylic formula fortified with urethane.

- Waterborne acrylic formula with urethane
- Specially formulated for use on all sealed hard surface flooring
- Keeps floors looking new
- Easy application with excellent levelling properties
- GREENGUARD certified





Bona[®] Professional Series Stone, Tile & Laminate Floor Refresher

Professional-level, acrylic coating formulated to keep, sealed hard-surface floors looking new

PHYSICAL CHARACTERISTICS

Ingredients – Water, acrylic polymer, urethane, wax, Diethylene Glycol Monoethyl Ether Color – Milky white (wet) pH –8.0 Solids – 10% - 12% Density – 8.39 lbs./gallon (1.01 S.G.) Gloss Level – (60°)>85 Odor – Non-Offending Flash Point – None Stability – 2 year shelf life VOC – Does not exceed 2% Packaging – 32 oz bottle

APPLICATION CHARACTERISTICS

Drying Time – 1 hour Application Tools – Bona® Microfiber Applicator Pad Coverage – 500 sq. ft. per bottle Clarity – Clear when dry Leveling – Excellent Percent Cured After 24 hours – 90% Defoaming – Excellent Max. Cure – 100% after 1 week

RECOMMENDED USE

Use every 3-4 months on all sealed hard surface flooring

DIRECTIONS

BEFORE USING, READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEET.

1. Remove furniture, rugs, etc. Vacuum sweep or dust mop, then thoroughly clean with Bona Stone, Tile & Laminate Floor Cleaner and the Microfiber Cleaning Pad on your Bona Mop. Allow the floor to dry. 2. Gently rock product back and forth to mix. Slightly dampen the Microfiber Applicator Pad with water and attach to mop. Squirt Stone, Tile & Laminate Floor Refresher onto the floor and spread. Work in sections small enough to keep the Applicator Pad wet. Continue working in sections until the entire floor is finished. Rinse Applicator Pad with water. 3. Allow to dry at least 1 hour before walking on the floor. For a glossier floor, a second coat may be applied after 2 hours. Allow 24 hours before heavy traffic.

For best results: Always test in an inconspicuous section of the floor before use. Coverage should be 500 square feet per bottle. Do not apply the product too thin or streaking will occur. Coat the entire floor to ensure an even appearance.

1. Clean 2. Squirt and Spread 3. Allow to Dry

CLEAN-UP

Clean all tools and equipment with warm water.

ORDERING INFORMATION

Item #	Description	No. Case	Size	Weight/Lbs.
WT760051164	Bona Pro Series STL Refresher	8	32 oz.	18.8

