



Bona SuperSport DTS®

Waterborne Sanding Sealer

Specially formulated waterborne sanding sealer for use with all Bona® waterborne finishes



Bona SuperSport DTS® is specially formulated waterborne sanding sealer for use with all Bona waterborne sport finishes. It seals the wood; develops a deep natural tone, vibrant look; abrades easily; and prevents the finish from penetrating into the wood surface.

- Excellent abrasability – hardens rapidly and allows for easy abrasion
- Seals the wood, preventing the finish from penetrating
- Minimizes side bonding
- Virtually odorless
- Fast drying
- Nonflammable
- GREENGUARD Gold certified for indoor air quality
- MFMA approved



Bona SuperSport DTS®

Waterborne Sanding Sealer

Specially formulated waterborne sanding sealer for use with all Bona® waterborne finishes

PHYSICAL CHARACTERISTICS

Ingredients - Water, polymeric resin, silica derivate, diethylene glycol monomethyl ether, propylene glycol.

Color – Milky white (wet)

pH – 7.5 - 7.9

Solids – 31-32%

Density – 8.66 lbs./gallon (1.04 S.G.)

US Regulatory VOC – 250 g/L

Odor – Non-offending

Stability – 1-year shelf life in an unopened container

Packaging – 5-gallon plastic pail

APPLICATION CHARACTERISTICS

Clarity – Clear when dry

Leveling – Excellent

Defoaming – Excellent

Drying Time – approximately 2-3 hours

Application Tools - Bona® Swivel Head Floor Coater and Bona Floor Coater Sleeve

Coverage – 450-550 square feet per gallon

Percent Cured After 24 Hours – N/A

Maximum Cure – 100% after one week

RECOMMENDED USE

Basketball courts, multi-purpose gym, stage, aerobic, dance and yoga floors, volleyball courts, racquetball, squash, and badminton courts.

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS.

FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

RESPONSE

In case of eye contact, flush immediately with water. Get medical attention if irritation occurs. For skin, wash thoroughly with soap and water. If affected by inhalation, remove to fresh air. If swallowed, drink 1 or

2 glasses of water to dilute. Do not induce vomiting. Get medical attention if symptoms.

COMPATIBILITY

Bona SuperSport DTS® will adhere to most stains, paints, sealers and finishes after proper preparation and dry times. Stain, sealer, paint, and finish results may vary widely depending on the wood species, especially on oily and resinous types. ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.

SANDING AND PREPARATION OF NEW FLOORS

1. Sand and prepare floor using MFMA-accepted methods. 2. Make your final cut with 100 to 120-grit paper. Screen with 120-grit screen or use a Bona MultiDisc and 120-grit Bona Diamond abrasives. 3. Vacuum thoroughly. 4. Dry tack thoroughly. 5. Apply sealer and finish system (see finish directions).

THE SUPERSPORT DTS SYSTEM:

Bona SuperSport DTS is a four-coat system: one or two coats of Bona SuperSport DTS, CourtLines® paint or Bona SuperSport Paint®, and two coats of a Bona Sport finish.

RECOMMENDED APPLICATORS

18" Bona Swivel Head Floor Coater with a Bona Floor Coater Sleeve.

NOTE

Use a clean applicator for the sealer and a separate clean applicator for finish.

MIXING INSTRUCTIONS

Remove lid and stir thoroughly before use.



Bona SuperSport DTS®

Waterborne Sanding Sealer

Specially formulated waterborne sanding sealer for use with all Bona® waterborne finishes

FINISHING

1. Pour a 4"-6" wide line of sealer along the starting wall. Go with the grain of the wood. 2. Using a clean, pre-dampened applicator; draw the applicator forward, with the grain of the wood, moving the sealer toward the opposite wall. Holding the applicator at a "snowplow" angle will help maintain a wet edge at all times. 3. At the end of each run, turn the applicator and pull it toward you through the puddle and pad out the applicator parallel to the wet edge. 4. Feather out all turns. Do not push too hard or too fast to avoid dripping or splattering. 5. Missed areas can be touched up if seen right away. 6. BE SURE YOU ARE USING THE RECOMMENDED COVERAGE OF 450-550 SQUARE FEET PER GALLON. DO NOT SPREAD TOO THIN. 7. Allow sealer coat to dry 2-3 hours. High humidity and/or low temperature conditions will extend the dry time (recommended conditions of 65-80°F/40-60% relative humidity). 8. Apply a Bona SuperSport finish.

INTERCOAT ABRASION FOR FLOORS WITH GAMELINES

Apply gamelines after the first coat of finish or a second coat of Bona SuperSport DTS. Before applying gamelines, abrade the floor using 240-grit Bona Diamond abrasives mounted on a Bona Conditioning Pad. Vacuum and tack thoroughly. Note: If paint will not be applied within 24 hours, the floor must be re-abraded to ensure proper adhesion. Apply gamelines using Bona CourtLines paint or Bona SuperSport Paint according to label instructions. If using another manufacturer's paint, before applying gamelines, always prepare a sample or test area to determine compatibility and adhesion. Always abrade properly dried Bona CourtLines paint using a Bona Conditioning Pad. If using Bona SuperSport Paint, there is no need to abrade if within 48 hours of the previous coat. Always vacuum and tack thoroughly after abrading. Apply finish coat within 24 hours.

INTERCOAT ABRASION FOR FLOORS WITHOUT GAMELINES

It is not necessary to abrade between Bona SuperSport DTS and Bona SuperSport finish coats unless more than 48 hours has passed since the previous coat was applied. For smoothest results, abrade between all coats as necessary. Always vacuum and tack thoroughly with a slightly water-

dampened Bona SuperCourt® mop and Bona SuperCourt Microfiber Wet Cleaning Pad after abrading.

CLEAN-UP

Clean application tools and equipment with mineral spirits.

STORAGE

Store at room temperature. Keep container closed when not in use. Do not store above 100° F (38° C). Do not transfer contents to other containers for storage and disposal. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

ORDERING INFORMATION

Item #	Description	Size	No. Case	Weight/Lbs.
WB254055001	Bona SuperSport DTS	5 Gallon	1	