

**BACK ON  
FLOOR IN  
12 H**

## Bona Traffic HD

### Finish/Lacquer

- ✓ Ultimate speed and durability
- ✓ Allows full traffic after 12 hours
- ✓ Easy and safe to apply
- ✓ Non-yellowing



4.54 L

Waterborne lacquer for wooden floors  
Wasserbasierte Beschichtung für Holböden  
Aqueux revêtement pour planches de bois  
Verfleur voor hout op vloeren

**Bona®**

*Schiphol Airport - Amsterdam*

# POWERFUL PERFORMANCE AT TOP SPEED

**Bona Traffic HD**



## Bona Traffic HD

### Powerful performance at top speed

Bona Traffic HD, the high-performance finish for high-traffic areas, now delivers superior protection in less time than ever before, outperforming any other finish in terms of speed and durability.

Experience unparalleled wear resistance and minimised downtime. Floor owners are now able to get back on the floor just 12 hours after application.

Bona Traffic HD is a powerful solution for areas such as lobbies, airports, exhibition halls and train stations, giving your floors long-lasting protection and preserving its beauty for its entire lifetime.

### APPLICATION

Designed to last, Bona Traffic HD ensures ultimate durability for extremely high-traffic areas.

- Heavy-traffic floors: airports, hotels, shopping malls etc.

### KEY BENEFITS

- Ultimate durability
- Minimises downtime – back on the floor in 12 hours
- Low VOC < 5%
- Extremely low odour
- Non-yellowing surface
- DIBt approved
- Excellent absorption of floor unevenness
- Improved adhesion for overcoating

### TECHNICAL DATA

<b>Type of varnish:</b>	2-component waterborne polyurethane topcoat
<b>Solids content:</b>	approx. 32%
<b>Sheen (at 60°):</b>	Silkmatt 40%, Matt 20%, Extra Matt 11% (on glass).
<b>Mixing ratio:</b>	1 part Hardener to 1 litre Traffic HD or 0.41 L Hardener to 4,54 L Traffic HD (≈8 vol%).
<b>Pot life:</b>	max. 4 hours at 20°C (shorter if warmer).
<b>Dilution:</b>	If required, dilute with 4% Bona Retarder for a longer open time.
<b>Drying time, until:</b>	- Recoating: 2-3 hours* - Light use: 6 hours* - Possible to cover: 3 days* <i>*under normal climate conditions, 20°C/60% R.H.</i>
<b>Application rate:</b>	8-10 m <sup>2</sup> /litre (100-120g/m <sup>2</sup> ) per coat
<b>Safety:</b>	Coating: Unclassified Hardener: Classified (see Safety Data Sheet)
<b>Cleaning:</b>	Wipe tools free from residual material before cleaning with a minimum of water. Dried material can be removed with acetone.
<b>Shelf life:</b>	<b>Coating:</b> 1 year from date of production in unopened original container. <b>Hardener:</b> 18 months from the date of production in unopened original container.
<b>Storage/transport:</b>	The temperature must not fall below +5°C or exceed +30°C during storage and transport.
<b>Disposal:</b>	Waste and emptied containers should be handled in accordance with local regulations.
<b>Pack size:</b>	3 x 4,95 litres incl. hardener (0,41 lit).