



# Bona Cleaner

## WOOD FLOOR CLEANER

Concentrated detergent for cleaning of finished wood and cork floors.



**Bona Cleaner** is a highly concentrated, slightly alkaline cleaner specifically designed for the cleaning of finished wood and cork floors. Bona Cleaner can be used for regular mopping or in a machine-based cleaning program.

- Specifically designed for lacquered wood and cork floors
- Efficient, low-foaming formula
- Leaves no dulling residue
- For daily maintenance and regular cleaning

### TECHNICAL DATA

pH-value:	Concentrate ca. 11
Base:	Solution of synthetic soaps
Dilution:	Normal cleaning: 0.5 dl to 5 liters of water (1%) Heavily soiled floors: 1 dl to 5 liters of water (2%)
Application tools:	Bona Cleaning Pad, cotton cloth, cleaning mop
Shelf life:	At least 2 years, from the date of production, in unopened original container
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size:	3 x 5 liters (44 boxes per pallet) 10 x 1 liters (50 boxes per pallet)

*Additional detailed information is noted in the appropriate Safety Data Sheet.*



# Bona Cleaner

## WOOD FLOOR CLEANER

**Concentrated detergent for cleaning of finished wood and cork floors.**

### PREPARATIONS

Remove loose dust/grit etc. using a vacuum cleaner, scissor mop or other dry-cleaning method.

### APPLICATION

Dilute concentrate according to recommendation and clean the floor using a mop or an auto scrubber equipped with a white or tan pad. Note that excessive use of water may damage the floor. Always keep the amount of water used to clean to a minimum and be careful where the floor has open gaps. Replace the cleaning water periodically to avoid streaking.

### AUTO SCRUBBER

Recommendations for use of auto scrubber:

1. Always fill the tank with clean water prior to use.
2. Run the machine along, never across, the parquet boards.
3. Water loss from the machine must not exceed 1 lit/100 m<sup>2</sup>. Test by adding 10 liters of water to the tank and check the remaining water after 100 m<sup>2</sup> (e.g. 5 x 20 m). 9 liters should remain in the tank.
4. Water should be removed promptly, make sure not to leave puddles when turning with the machine.
5. If distributing water with the machine, the water must be removed within 3 minutes.
6. Keep the rubber band clean and in good trim. Replace annually or if the machine is leaving puddles or too much water.
7. Do not use aggressive pads on the surface. Aggressive pads may scratch and wear on the surface. The milder the pad, the lesser the wear.