



Bona Decking Oil

OUTDOOR IMPREGNATING OIL

Long lasting protection against the weather



Outdoor oil for superb impregnation and lasting protection of decks and exterior woodwork.

Bona Decking Oil provides outdoor decking with long-lasting protection against all forms of weather, from snow to sunlight. Its unique formula enhances the natural wood grain, while reducing the risk for cracking and warping. It also contains UV protection against bleaching. With easy application and quick drying, it is the perfect partner for outdoor decking protection.

- Excellent water repellence
- Reduces cracking and warping
- Fast drying
- Long-lasting protection



Bona Decking Oil

OUTDOOR IMPREGNATING OIL

Long lasting protection against the weather

TECHNICAL DATA

Product type / base:	Modified vegetable oil
Colours:	Neutral, Mahogany, Teak & Grey.
Drying time:	Between applications: 30-60 minutes ¹ Light use: 24 hours ¹
	¹ under normal climate conditions, 20°C/60% R.H.
Application tools:	Brush, roller or other suitable applicator.
Application rate:	Approx. 20 m ² /litre dependant on wood species.
Fire risk:	Non-flammable, however risk of self-ignition exists. Used cloths, paper, rags and similar should be immersed in water or placed in sealed metal containers. See Safety Data Sheet.
Safety:	Unclassified
Cleaning:	Clean tools with white spirit. Dried material can be removed with white spirit.
Shelf life:	2 years from date of production in unopened original container.
Storage/Transport:	The temperature must not fall below +5°C or exceed +30°C during storage and transport. Store in a cool place.
Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Pack size:	2.5 litre containers (all colours) 10 litre container (neutral only)

Additional detailed information is noted in the appropriate Safety Data Sheet.

PREPARATION

The surface which is to be treated must consist of bare wood and be dry. Oiled, waxed and/or decayed wood should be thoroughly cleaned with Bona Deep Clean Solution or Bona Decking Reviver prior to applying new oil.

Moisture content of the wood should not exceed 18% RH.

Newly installed wood decking must not be treated

immediately after installation but must first be exposed to several weeks of weathering. This makes the wood porous and absorbent for the Bona Decking Oil.

Optimal application conditions are between 18-25°C. High temperature and low humidity shortens the drying time, low temperature and high humidity prolongs the drying time. **Minimum temperature for use is 13°C.**



Bona Decking Oil

OUTDOOR IMPREGNATING OIL

Long lasting protection against the weather

APPLICATION

1. Stir the can well.
2. Apply 1-2 coats of the oil evenly and thinly using a wide brush or other suitable applicator.
3. When the decking is saturated, wipe off all surplus oil with a cotton cloth.
4. Allow at least 24 hours drying time before taking the decking into use. Avoid foot traffic during this time. If it

rains on the decking before the oil has hardened, it may be necessary to re-apply a thin layer of oil.

Drying time (at 20°C/60% RH): 24 hours, expect longer drying time on exotic wood and at low temperatures and/or high relative humidity.

WARNING: BONA DECKING OIL CONTAINS DRYING OILS. RISK OF SELF-IGNITION. USED CLOTHS, PAPER, RAGS AND SIMILAR SHOULD BE PLACED IN WATER OR SEALED METAL CONTAINERS

MAINTENANCE

Rinse decking on occasion with soap and water. If it starts to show signs of wear i.e., a lighter, dryer appearance then it is possible to apply an additional layer of Bona Decking Oil to improve the surface and extend the life

before a full re-application is required. Grey, decayed wood should be thoroughly cleansed with Bona Deep Clean Solution or Bona Decking Reviver prior to re-oiling.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.