



Bona DriFast® Stain

OIL-MODIFIED STAIN FOR INTERIOR HARDWOOD FLOORS.

Provides speed and high performance for hardwood floor finishing



A premium quality, oil-modified stain for interior hardwood floors. Provides speed and high performance for hardwood floor finishing professionals.

Bona DriFast® Stain oil-modified formula is easy to apply and great to work with. There's enough open time to rework an area, or blend in sections of cut-up jobsites without worrying about lap marks. Bona DriFast Stains are also compatible with all Bona finish systems, including waterborne. Four beautiful collections with 26 colors capture the invigorating spirit of great design. All 26 colors are available in quart and gallon sizes. Stand out against the competition by providing a unique offering from the latest color trends!

- No bleed back and no lapping
- Penetrates, stains, and seals bare wood
- Easy touch-ups after initial application
- Blendable to achieve unlimited custom colors



Bona DriFast® Stain

OIL-MODIFIED STAIN FOR INTERIOR HARDWOOD FLOORS.

Provides speed and high performance for hardwood floor finishing

TECHNICAL DATA

Ingredients:	Wood tones: Oil-modified resins, mineral spirits (solvent), pigments, driers. White: Oil-modified resins, mineral spirits (solvent), titanium dioxide, fillers
Solid Content:	35-47%
Density:	Wood tones: 7.2-7.5 lbs./gallon (0.86-0.90 sg), White: 8.7-9.0 lbs./gallon (1.04-1.8 sg)
US Regulatory VOC:	550 g/L
Odor:	Mild solvent odor
Color:	Wood tones: Natural, Golden Oak, Nutmeg, Early American, Provincial, Special Walnut, Rosewood, Red Mahogany, Jacobean, Graphite, Medium Brown, Antique Brown, Puritan Pine, Cherry, Sedona Red, Spice Brown, Grey, Ebony, Bark, Cocoa, Driftwood, Birch, Aged Pewter, Twig and Sand Dune.
Packaging:	1-quart can, 1-gallon can
Shelf life:	Two-year shelf life in unopened container
Storage/Transport:	Store at room temperature. Keep container closed when not in use. Do not store above 100°F (38°C). Do not transfer contents to other containers for storage and disposal. In case of spillage, absorb with inert material.
Application Tools:	Brush, cut-in pad, clean cloth, carpet disc
Coverage:	800-1,000 square feet per gallon
Drying time:	2 hours for wood tones, 6 hours minimum for white and 12-18 hours for Ebony, Spice Brown, Bark and Cocoa under ideal conditions of 60-80° F (16°-27°C) with 35-75% relative humidity.
Clean-up:	Clean applicator tools and equipment with mineral spirits.
Disposal:	Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS. FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

HAZARD WARNING: RAGS, STEEL WOOL OR WASTE SOAKED WITH BONA DRIFAST STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED, METAL CONTAINER.



Bona DriFast® Stain

OIL-MODIFIED STAIN FOR INTERIOR HARDWOOD FLOORS.

Provides speed and high performance for hardwood floor finishing

RESPONSE

Get medical attention if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately

call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention.

RECOMMENDED USE

Prepares the surface for a topcoat of Bona® waterborne or any other Bona® finish. Apply only over bare wood.

FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

COMPATIBILITY

Stain, sealer, and finish results may vary widely depending on the wood species, especially on oily and resinous exotics. ALWAYS PREPARE A SAMPLE OR TEST AREA TO

DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS

BONA PRODUCT SYSTEM

DriFast® Stain System

Bona DriFast Stain is a redissolving stain designed to penetrate, stain and seal bare wood. Bona DriFast Stain is

designed to work with all bona finishes. Colors may be blended with all other Bona DriFast Stains. Visit www.bona.com for additional product information

PREPARATION

1. Sand and prepare floor using accepted industry association methods. 2. Make your final cut with 80 to 100-grit paper and MultiDisc with an 80 to 120-grit. 3. Use a

Tampico Brush on a buffer and vacuum thoroughly. 4. Tack with a dry Bona® Microfiber Mop or cloth to remove dust. 5. Apply stain system.

MIXING INSTRUCTIONS

SHAKE AND STIR WELL BEFORE USING. DO NOT THIN.



Bona DriFast® Stain

OIL-MODIFIED STAIN FOR INTERIOR HARDWOOD FLOORS.

Provides speed and high performance for hardwood floor finishing

APPLICATION

1. After preparing surface, apply Bona DriFast Stain with brush, cut-in pad, cloth, or carpet disc driven by a buffer in the direction of the grain at the coverage rate of 800 – 1000 square feet per gallon. 2. Allow 1-3 minutes for penetration. Remove excess by hand wiping or buffing with an absorbent, non-abrasive material. 3. Allow stain to dry thoroughly (minimum 2 hours for wood tones, 6 hours minimum for white and 12-18 hours for Ebony, Spice Brown,

Bark and Cocoa under ideal conditions of 60°-80° F(16°-27°C) with 35-75% relative humidity. High humidity and/or low temperature conditions will extend dry time, while increased ventilation and airflow will reduce dry time. Apply sealer or finish after the recommended dry time, but within 48 hours after application. 4. Apply any Bona finish system over thoroughly dried stain.

Bona US
24 Inverness Place East, Suite 100
Englewood, Co. 80112