



Bona Oil Care

WOOD FLOOR MAINTENANCE

For protection and revival of oiled wood floors



For protection and revival of oiled wood floors

Bona Oil Care is a rapid drying maintenance oil for protecting and reviving oiled wood floors. Formulated to keep the solvent content to a minimum while maintaining user-friendliness and product performance. Consists of a low-viscous blend of different plant-based oils with excellent penetration ability. Replenishes the wood pores for sustained protection.

- Restores and protects
- Low viscosity
- Excellent penetration
- Safe for application on children's toys



Bona Oil Care

WOOD FLOOR MAINTENANCE

For protection and revival of oiled wood floors

TECHNICAL DATA

Product type / base:	Modified, plant-based oils.
Colours:	Neutral
Dilution:	Do not dilute.
Drying time:	Minimum 12 hours under normal indoor conditions, 20° C/60% R.H. Ensure proper ventilation.
Application tools:	Bona WoolPad or white pad
Cleaning:	Clean tools with white spirit. Dried material can be removed with white spirit.
Shelf life:	3 years, from date of production, in unopened original container
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Pack size:	3 x 5 litres, tin can (44 boxes per pallet) 6 x 1 litre, plastic can (60 boxes per pallet)

Additional detailed information is noted in the appropriate Safety Data Sheet.

PREPARATION

If necessary, the previously oiled surface must be thoroughly cleaned with Bona Oil Soap or the Bona Deep Clean Solution, and allowed to dry, prior to application of

oil. Allow product to reach room temperature and shake the container thoroughly before use. Minimum temperature for use is 16°C.

DIRECTIONS FOR USE

1. Distribute the oil thinly on a section of the floor using a Bona WoolPad or a white pad fitted under a buffing machine
2. Without delay, remove surplus material with cotton

cloths and let the surface dry for minimum 12 hours. Expect longer drying time on dense, exotic wood and if the temperature is low.

WARNING: BONA OIL CARE CONTAINS DRYING OILS. RISK OF SELF-IGNITION. USED CLOTHS, RAGS, WOOL PADS AND SIMILAR MATERIAL SHOULD BE PLACED IN WATER OR SEALED METAL CONTAINERS.



Bona Oil Care

WOOD FLOOR MAINTENANCE

For protection and revival of oiled wood floors

CONSUMPTION

~50-100 m²/litre depending on the condition of the floor

MAINTENANCE

Clean the floor regularly using a dry mop and/or a vacuum cleaner. When needed, wipe off with a damp mop with Bona Oil Soap added to the cleaning water. Always clean using as dry a method as possible. Apply Bona Oil Care frequently to ensure that the pores of the wood remain saturated and unable to pick up dirt and moisture. The

frequency of this operation is determined by the level of wear and may range from every 3rd year in a domestic environment to a few times a year in a commercial environment. Detailed maintenance instructions are available at www.bona.com

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.