

Bona Pacific Filler®

HIGH SOLIDS, WATERBORNE WOOD FILLER

High solids, waterborne compound designed for hardwood floors



A ready-to-use waterborne wood floor filler for spot or full-trowel filling.

Bona Pacific Filler® is a high solids, waterborne compound specifically designed for filling cracks, holes, chips, gouges, and broken edges in hardwood floors prior to finishing. It is a ready-to-use formula, for spot or full-trowel filling. It has excellent adhesion, staining, and finishing properties with minimal shrinkage. For more accurate color matching, Bona Pacific Fillers can be blended together, tinted with universal tints, or mixed with fine edger dust to achieve the closest match possible.

- Thicker formula
- Sands easily
- Minimal clogging of sandpaper
- Accepts stain like wood

Bona Pacific Filler®

HIGH SOLIDS, WATERBORNE WOOD FILLER

High solids, waterborne compound designed for hardwood floors

TECHNICAL DATA

Ingredients:	Inorganic fillers, water, binders, pigments
Solid Content:	65-75%
Density:	13.3 lbs./gallon (1.60 SG)
US Regulatory VOC:	100 g/L
Odor:	Mild Latex odor
Color:	Red Oak, White Oak, Ash-Maple-Pine
Packaging:	All colors available in gallons and 3.5-gallon pails
Shelf life:	One year shelf life in unopened container
Storage/Transport:	Store at room temperature. Keep container closed when not in use. Do not store above 100° F (38° C).
Application Tools:	Bona Steel Trowel, putty knife
Coverage:	600-800 square feet per gallon
Drying time:	30 minutes to 2 hours, depending on environmental conditions (temperature and humidity), coverage rate, and size of cracks and holes.
Clean-up:	Clean tools with water
Disposal:	Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS. FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

RESPONSE

In case of eye contact, flush immediately with water. Get medical attention if irritation occurs. For skin, wash thoroughly with soap and water. If affected by inhalation,

remove to fresh air. If swallowed, drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Get medical attention if symptoms occur.

RECOMMENDED USE

Apply over bare wood before the final sanding cut.
Formulated for use with all Bona finishing systems. Always

prepare a test sample on a small area to determine compatibility and color acceptance

Bona Pacific Filler®

HIGH SOLIDS, WATERBORNE WOOD FILLER

High solids, waterborne compound designed for hardwood floors

COMPATIBILITY

Bona Pacific Filler will accept most stains, sealers and finishes in the same manner as most woods. ALWAYS PREPARE A TEST OR SAMPLE AREA TO DETERMINE

COMPATIBILITY. Do not use wood bleach over Bona Pacific Filler as it may damage the filler.

BONA PRODUCT SYSTEM

Bona Pacific Filler brand hardwood floor filler is a high solids content, waterborne compound specifically designed for filling cracks, holes, chips, gouges, and broken edges in

hardwood floors prior to finishing. This product has excellent adhesion, staining and finishing properties with minimum shrinkage.

PREPARATION

Sand and prepare floor using accepted industry association methods.

MIXING INSTRUCTIONS

Stir thoroughly before using. One to two cups of water may be added per gallon.

APPLICATION

Apply Bona Pacific Filler before final sanding with the drum or belt machine. Thoroughly vacuum dust from cracks and holes before filling. Work the filler as deep as possible into cavities. To fill and level larger holes or deeper cracks, several applications may be required. It may be necessary to trowel-fill the entire floor, depending upon the extent of cracks between strip or parquet floors. Allow sufficient drying time: 30 minutes to 2 hours before final sanding. Higher

humidity or cooler conditions will increase the drying time.

Tip: Bona Pacific filler can be tinted using universal tints. Do NOT exceed 1 ounce per gallon of Pacific Filler.

Alternatively, fine wood dust (80-120 grit) and water can be used to adjust the color. Do NOT exceed more than 1 cup of water per 1 gallon of Pacific Filler.

Bona US
24 Inverness Place East, Suite 100
Englewood, Co. 80112