



Bona Polish

WATERBORNE COATING FOR FREQUENT MAINTENANCE

Wood Floor Maintenance



Waterborne coating for frequent maintenance

Bona Polish (Gloss & Matt) is a ready-to-use maintenance coating designed for lacquered wood flooring but with the flexibility of being possible to use on a variety of flooring types. Bona Polish fills up micro scratches and produces a sacrificial wear layer that protects the original surface. Bona Polish is reinforced with polyurethane for increased resistance to wear and is suitable for both domestic and commercial environments.

- Possible to use on a variety of floors including varnished floors, laminate, linoleum, PVC and ceramic tiles.
- Reinforced with polyurethane for increased durability.
- Excellent flow
- Meets EN 14904:2006 (only gloss version)



Bona Polish

WATERBORNE COATING FOR FREQUENT MAINTENANCE

Wood Floor Maintenance

TECHNICAL DATA

Product type / base:	Waterborne acrylate & polyurethane mix dispersion
Sheen:	Gloss, matt
Dilution:	Do not dilute, product is ready-to-use
Drying time:	approx. 1 hour at 20 °C & 60 % RH
Application tools:	Polish Applicator Pad
Cleaning:	Clean tools with a minimum of soap and water, dried stains can be removed with Bona Remover or acetone. Dispose of all waste at an approved waste disposal facility - do not pour down drains or sewers.
Shelf life:	Gloss: 2 years, from date of production, in unopened original container Matt: 1 year, from date of production, in unopened original container.
Storage/Transport:	The temperature must not fall below +5 °C or exceed +30 °C during storage and transport. Store in a cool place.
Disposal:	Containers with a minimal amount of dried material may be recycled. All waste must be disposed of at an approved waste disposal facility - do not pour down drains or sewers. Follow all local waste regulations.
Pack size:	3 x 5 litres (44 boxes per pallet) 6 x 1 litre (90 boxes per pallet)
Certificates & standards:	EN 14904 - Multi-sport surfaces (Gloss only)

Additional detailed information is noted in the appropriate Safety Data Sheet.

PREPARATION

Remove loose dirt and grit from your floor. Depending on the degree of soiling, mix a suitable solution of Bona Cleaner or Bona Deep Clean Solution and wet clean the floor thoroughly. Note that any remaining dirt will become trapped in the coating and cannot be removed afterwards. Let floor dry completely.

Do not use Bona Polish on any floor that has been waxed or oiled as residues from these materials may disrupt the adhesion to the surface. It is recommended to always test the adhesion to the surface and check for desired results prior to using Bona Polish.



Bona Polish

WATERBORNE COATING FOR FREQUENT MAINTENANCE

Wood Floor Maintenance

DIRECTIONS FOR USE

1. Shake the container thoroughly before use. Apply polish in a 3-4 cm wide wavy line on a 3 m² section of the floor and without delay, spread the product using a flat polish application pad. For best results, maintain a thin consistent coat.
2. Without adding more product, smooth out the section by moving the applicator with the grain of the wood.
3. Continue section by section and when complete allow the

treated floor a minimum of 1 hour drying time before resuming light foot traffic. If needed, a second coat of polish can be applied after 2 hours.

Avoid heavy traffic and the replacement of furniture and rugs until next day. To achieve a uniform appearance, it is advised to always treat the entire surface.

CONSUMPTION

~ 50 m²/litre

MAINTENANCE

Wet cleaning of the floor may be carried out after 3 days drying. For regular cleaning use Bona Cleaner. Do not use

strongly alkaline cleaning agents as they may damage the floor or remove the protective coating of polish.

TIPS

- When smoothing out the product, keep the applicator pad flat to the surface and apply from wall-to-wall. Avoid lifting the applicator along the way as this produces bubble.
- Do not work into areas starting to dry as this may produce

streaking.

- If applying multiple layers of polish, do not rush the drying time between coats there is a high risk of dissolving the previous layer.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.