Bona Stone, Tile & Laminate Polish

Technical data sheet

Bona Stone, Tile & Laminate Polish is a ready-to-use waterborne maintenance coating for a large variety of hard surface floors including laminate flooring, vinyl linoleum, unglazed tile (ceramic, quarry), stone and sealed marble. It gives new shine while offering extended protection against wear.

- Durable, reinforced with polyurethane
- · Easy and safe to use
- Works with a wide range of surfaces
- Quick drying

Technical data

Binding agent: Acrylate/polyurethane

Gloss: High gloss
Dilution: Do not dilute

Drying time: - Touch dry: 30-60 minutes

- Recoatable: minimum 2 hours

Application tools: Bona Applicator Pad Coverage: Approx. 50 m²/litre

Safety: The product is not classified according to European Regulation

(EC) 1272/2008 and its amendments.

Clean tools with water directly after use. Dried material can be

removed with acetone.

Shelf life: 2 years from date of production in unopened original container Storage/transport: The temperature must not fall below +5°C or exceed +25°C

during storage and transport.

Disposal: Wastes and emptied containers should be handled in

accordance with local regulations.

Sizes: 1L

Certification: Greenguard

Preparations

Remove loose dirt and grit from your floor. Clean floor thoroughly with Bona Stone, Tile & Laminate Cleaner and let dry. Do not use over any floor that has been waxed or oiled. Wax and oil residues will prevent proper adhesion of Bona Tile & Laminate Polish to floor. If uncertain, perform a small test before use.

Shake bottle thoroughly before use. Apply at normal room temperature, 18-25 $^{\circ}\text{C}.$

Instructions for use

- 1. Pour a wide line of Stone, Tile & Laminate Polish on a small section of the floor.
- 2. Spread the product over the section using a Bona Applicator Pad.
- 3. Complete section by smoothing with the applicator pad in the same direction throughout the floor area.
- 4. Continue section by section until the whole floor has been treated.

The floor can be walked on after 2 hours but avoid heavy traffic and replacement of furniture and rugs the first 12 hours.







Bona Stone, Tile & Laminate Polish

Technical data sheet

Maintenance

Clean floor with Bona Stone, Tile & Laminate Cleaner and a Bona Cleaning Pad. When the floor is starting to show signs of wear and needs freshening up, clean and apply a new layer of Bona Stone, Tile & Laminate Polish. For removal of polish build up use Bona Polish Remover.

For more information, please visit bona.com

